



CRYOCLEAN® snow. SJ-25 CO₂ snow blasting machine.

- For large surfaces and stubborn contaminations
- Powerful round nozzles
- Flat nozzles with blasting widths of up to 100 mm (4")
- Available in desktop and trolley versions
- No electric power supply (powered pneumatically)



Pistol holder can be fixed to handhold



Large pneumatic tyres



Removable handhold



Safe supply connectors

Technical data

Desktop dimensions – L x W x H	580 mm x 370 mm x 470 mm (22.8" x 14.6" x 18.5")
Desktop weight	25.6 kg (56.4 lb)
Trolley dimensions – L x W x H	620 mm x 490 mm x 970 mm (24.4" x 19.3" x 38.2")
Trolley weight	33.2 kg (73.2 lb)
Compressed air consumption	1–6 m ³ /min (35 to 212 scf/min)
Compressed air operating pressure	5–16 bar (72 to 232 psi)
Compressed air connection	DIN 3489, customer-specific
Compressed air quality	Dry; no oil or particles
Liquid CO ₂ consumption	0.4 to 1.5 kg/min (0.9 to 3.3 lb/min)
Liquid CO ₂ operating pressure	20 to 100 bar (290 to 1,450 psi)
Liquid CO ₂ connection	DIN 477 – W 21.8 x 1/14", customer specific
Blasting pressure	2 to 16 bar (29 to 232 psi)
Sound power level	80 to 110 dB(A)

Linde GmbH

Gases Division, Dr.-Carl-von-Linde-Strasse 6–14, 82049 Pullach, Germany
Phone: +49 89 7446 0, cryoclean@linde.com, www.linde-gas.com